

# STOP OVERCOOLING. START DRYING.

Industry experts agree energy efficient building techniques have reduced air conditioning runtime, resulting in the need for dedicated dehumidification in homes. Overcooling to control relative humidity isn't effective or economical and can lead to comfort and health issues.

Dedicated to better IAQ, Santa Fe Ultra Series dehumidifiers efficiently and effectively protect the home and create a living space that is both healthy and comfortable.

Santa Fe Ultra Series dehumidifiers integrate directly with the HVAC system to provide:

- Dedicated dehumidification for the entire home, regardless of AC runtime
- Fresh air intake/ Outdoor air ventilation
- Superior MERV-13 filtration
- Unmatched Warranty-20 percent longer than any competitor

Santa-Fe dehumidifiers are engineered and assembled in Madison, WI by Therma-Stor LLC.

We take pride in building the highest quality products and stand behind every one. Our legacy of innovation and commitment to excellence for over 40 years is what sets us apart.

## Santa Fe Stand-Alone Dehumidifiers



**Compact70**



**Oasis™ 105**



**Advance Dry110**



**Classic**



**SANTA-FE™**  
INDOOR AIR QUALITY SOLUTIONS

**DEDICATED  
DEHUMIDIFICATION**

**+**

**FRESH AIR  
VENTILATION**

**+**

**SUPERIOR  
FILTRATION**



**SANTA-FE™**  
INDOOR AIR QUALITY SOLUTIONS

Contact us: [Santa-Fe-Products.com](http://Santa-Fe-Products.com) or 800-533-7533

[Santa-Fe-Products.com](http://Santa-Fe-Products.com)



**SANTA-FE™**  
INDOOR AIR QUALITY SOLUTIONS



**Ultra 70**

**Ultra V100**

**Ultra V125**

**Ultra V155**

**Ultra V205**

**Ultra MD33**

<b>WATER REMOVAL</b>	@ 80°F / 60%RH 70 PINTS/DAY 8.75 GALLONS/DAY @ 73°F / 60%RH 55 PINTS/DAY 6.875 GALLONS/DAY	@ 80°F / 60%RH 100 PINTS/DAY 12.6 GALLONS/DAY @ 73°F / 60%RH 82 PINTS/DAY 10.25 GALLONS/DAY	@ 80°F / 60%RH 125 PINTS/DAY 15.5 GALLONS/DAY @ 73°F / 60%RH 101 PINTS/DAY 12.6 GALLONS/DAY	@ 80°F / 60%RH 155 PINTS/DAY 19.3 GALLONS/DAY @ 73°F / 60%RH 128 PINTS/DAY 16 GALLONS/DAY	@ 80°F / 60%RH 205 PINTS/DAY 25.625 GALLONS/DAY @ 73°F / 60%RH 173 PINTS/DAY 21.6 GALLONS/DAY	@ 80°F / 60%RH 37 PINTS/DAY 4.6 GALLONS/DAY @ 65°F / 60%RH 22 PINTS/DAY 2.75 GALLONS/DAY
<b>EFFICIENCY</b>	@ 80°F / 60%RH 5.5 PINTS/KWH @ 73°F / 60%RH 4.31 PINTS/KWH	@ 80°F / 60%RH 6.4 PINTS/KWH @ 73°F / 60%RH 5.55 PINTS/KWH	@ 80°F / 60%RH 5.9 PINTS/KWH @ 73°F / 60%RH 5.2 PINTS/KWH	@ 80°F / 60%RH 7.1 PINTS/KWH @ 73°F / 60%RH 6.5 PINTS/KWH	@ 80°F / 60%RH 7.5 PINTS/KWH @ 73°F / 60%RH 6.3 PINTS/KWH	@ 80°F / 60%RH 5.1 PINTS/KWH @ 65°F / 60%RH 3.46 PINTS/KWH
<b>ENERGY FACTOR</b>	@ 80°F / 60%RH 2.6 L/KWH @ 73°F / 60%RH 2.04 L/KWH	@ 80°F / 60%RH 3.0 L/KWH @ 73°F / 60%RH 2.63 L/KWH	@ 80°F / 60%RH 2.8 L/KWH @ 73°F / 60%RH 2.45 L/KWH	@ 80°F / 60%RH 3.35 L/KWH @ 73°F / 60%RH 2.9 L/KWH	@ 80°F / 60%RH 3.5 L/KWH @ 73°F / 60%RH 3.0 L/KWH	@ 80°F / 60%RH 2.4 L/KWH @ 65°F / 60%RH 1.64 L/KWH
<b>CURRENT DRAW</b>	4.1 AMPS @ 73°F / 60%RH	5.4 AMPS @ 73°F / 60%RH	7.0 AMPS @ 73°F / 60%RH	7.1 AMPS @ 73°F / 60%RH	12.5 AMPS @ 73°F / 60%RH	2.2 AMPS @ 65°F / 60%RH
<b>BLOWER</b>	150 CFM @ 0.0" WG 140 CFM @ 0.2" WG 130 CFM @ 0.4" WG	385 CFM @ 0.0" WG 350 CFM @ 0.2" WG 305 CFM @ 0.4" WG	385 CFM @ 0.0" WG 350 CFM @ 0.2" WG 305 CFM @ 0.4" WG	435 CFM @ 0.0" WG 395 CFM @ 0.2" WG 360 CFM @ 0.4" WG	550 CFM @ 0.0" WG 515 CFM @ 0.2" WG 470 CFM @ 0.4" WG	155 CFM @ 0.0" WG
<b>REFRIGERANT</b>	R454B	R454B	R454B	R454B	R454B	R454B
<b>AIR FILTER</b>	MERV-13	MERV-13	MERV-13	MERV-13	MERV-13	WASHABLE
<b>DIMENSIONS WITH COLLARS</b>	12.00" W 12.00" H 28.00" D	14.35" W 24" H 39.25" D	14.35" W 24" H 39.25" D	14.35" W 24" H 39.25" D	26.75" W 20.75" H 38" D	14.19" W 30.00" H 5.75" D
<b>WEIGHT</b>	55 LBS.	101 LBS.	104 LBS.	112 LBS.	148 LBS.	39 LBS.
<b>SIZING*</b>	UP TO 1,800 FT <sup>2</sup>	UP TO 2,300 FT <sup>2</sup>	UP TO 3,000 FT <sup>2</sup>	UP TO 3,500 FT <sup>2</sup>	UP TO 5,000 FT <sup>2</sup>	UP TO 1,200 FT <sup>2</sup>
<b>WARRANTY</b>	6 YEARS	6 YEARS	6 YEARS	6 YEARS	6 YEARS	6 YEARS

\*RECOMMENDED FT<sup>2</sup> BASED ON 8'-10' CEILINGS



Ultra Series dehumidifiers can be controlled comfortably from the living space using the **Ultra Series DEH3000 Digital Control**. Remote sensing option also available with the Ultra Series DEH3000R and the **SmartAire™ Remote Sensor** (select models only).

